

HD10 Hook Panel Specifications

PART 1 - GENERAL

1. DESCRIPTION: Furnish and install wall mounted hook panels.
2. RELATED WORK: (Refer to Section of Specs which applies to wall blocking.)

PART 2 - PRODUCTS

1. MANUFACTURER: (specify 2HD10, 3HD10, 4HD10, 6HD10, or custom D10 hook panel) series hook panel by EMCO Specialty Products, Inc., Kansas City, KS.
2. MATERIALS: Panel shall be of solid (walnut, oak, or maple) 5/8" x 3 3/4" hardwood and drilled for hooks. The finish is to be (specify walnut, medium oak, light oak, maple, or unfinished oak).
3. HD10 panels shall have (specify two, three, four, or six) hooks (specify finish either silver, almond, antique brass, dark brown, black) arranged as per manufacturer's standards (unless custom quantities are prescribed by the Architect) All hooks to be installed at the factory.

PART 3 - EXECUTION

INSTALLATION:

1. Install wall blocking.
2. Installation procedures will vary depending on length of panel.
3. Install using "fasteners by others" appropriate for wall type.
4. Install panel at height specified by architect.
5. Check to make sure the panel is level.
6. Wipe down panel to remove dust.
7. Remove all trash and debris.